



HCT-200BP2

RoHS
2002/95/EC

Technical Specification

HALL EFFECT CURRENT TRANSDUCER 200A OPEN LOOP
VOLTAGE OUTPUT

Edition	Changed by	Date	Change description
1 st	V.Repecho	05/03/09	First edition



HCT-200BP2

RoHS
2002/95/EC

2. Electrical Parameters

Primary Nominal Current	200 A DC	I_{p-n}
Measuring Range	± 600 A DC	I_p
Secondary Nominal Voltage	4 V $\pm 1\%$ RMS	V_s
Supply Voltage ($\pm 5\%$)	± 15 V	V_{cc}
Current Consumption	12 mA ($V_{cc} = \pm 15$ V)	I_{cc}


3. Accuracy

Accuracy at I_p $T = 25$ °C	$< \pm 1\%$	a
Linear Error (2 to I_{pn})	$< 1\%$	e_{LLR}
Offset Voltage	± 25 mV Max	V_{OS}
Offset Voltage Drift	± 0.5 mV/°C	KI_{OS}
Time Response (10% to 90% of I_p) Related to di/dt Specified	< 3 μ s	T_R

- * Electrical Parameters and frequency response to be checked with samples.



HCT-200BP2



4. Output Connector

Connection	PTH	
------------	-----	--

5. General Data

Operating Temperature	-40 to +85 °C	T_A
Storage Temperature	-55 to +125 °C	T_S
Weight	65 g	
Basic Insulation (Between Primary and Measurement Current)	2500 V AC 50Hz 1'	V_I

6. Standards

-

7. Packaging

- Single Packaging.

END OF DOCUMENT