
















Accessories - Heatsinks

Type	Suitable for	R_{thsa} natural cooling	R_{thsa} forced air or water cooling	w	w	Picture
		K/W	K/W	kg	kg/m	
Forced-air cooled						
N 4	Capsules	-	0.04	-	25.1	
P 1	Studs or modules	0.7	0.4	-	11.3	
P 3	Isolated base modules	0.45	0.14	-	17.6	
P 8 ¹⁾	Capsules	0.35	0.07	-	9.6	
P 8,5 ¹⁾	Capsules	0.3	0.08	-	9.5	
P 9 ¹⁾	Capsules	0.21	0.06	-	17.8	
P 11	Capsules	0.2	0.05	-	15	
P 16	SKiIP or modules	-	0.06	-	23.5	
P 17	Capsules	0.45	0.12	-	10.6	
P 18	Capsules	0.37	0.08	-	12.2	
P 21 ¹⁾	Isolated base modules	-	0.02	-	40.8	
Px 308 ¹⁾	SKiIP or modules	-	0.013	-	12.2	
R 4A	Isolated base modules	1.4	0.38	0.6	-	




Accessories - Heatsinks

Type	Suitable for	R_{thsa} natural cooling K/W	R_{thsa} forced air or water cooling K/W	w kg	w kg/m	Picture
Forced-air cooled						
U 3	Capsules	0.14	0.06	-	23.7	
Natural cooled						
P 4 ¹⁾	Stud device	0.27	-	-	20.6	

footnotes

¹⁾ Non standard item, available on request only, typical minimum batch quantities of 60 pieces will apply

Accessories - Fans

Type	V _{in} V	f Hz	V _{air} / t m ³ /h	P _{max} V	T _{Amax} °C	w kg	Noise dB	Picture
Axial Fans								
SKF 3-230-01	230	50	159 / 190	15 / 14	70	0.55	37 / 41	
Centrifugal Fans								
SKF 17 A-230-11	230	50	850 / 930	110 / 120	70	2	74	
SKF N4-230-01	230	50	1500 / 1700	210 / 280	80 / 70	3.1	76 / 78	
Radial Fans								
SKF 16 A-230-01	230	50	615 / 575	135 / 154	50 / 40	3.6	55 / 57	
SKF 16 A-230-11	230	50	615 / 575	135 / 154	50 / 40	3.6	55 / 57	
SKF 16 B-230-01	230	50	610 / 565	170 / 197	40	3.6	58 / 57	